



PET TAPE - SINGLE SIDED

Product Features

PET tape is made of PET film as base material, coated with special semi-sensitive adhesive on one side

Application

Can be used for mobile phone frame fixing, flat film switch bonding, automotive industry's ABS plastic parts fixing, rubber EPDM bonding, batteries in electronic equipment and lenses and windows' bonding, signage fixed, LCD reflective film splicing plastic film, low-energy plastic material bonding



White

Product Characteristics

- Scratch-proof, waterproof, easy to peel, no residue
- Reworkable, removable, good bonding strength for most materials, good initial viscosity

Product Sizes

* Contact sales representative for available sizes

Technical Data

Product	Structure (from Top to Bottom)	Adhesive	Thickness	180° Peeling Force	Temperature resistance
			(mm)	(N/inch)	(°C)
G452		Acrylic pressure sensitive Adhesive	0.065	>5	- 5-160
H448		Acrylic pressure sensitive Adhesive	0.125	>22	- 5-160
L1237		Acrylic pressure sensitive Adhesive	0.17	>15	- 5-160
6205		Acrylic pressure sensitive Adhesive	0.05	>10	- 5-100
6208		Acrylic pressure sensitive Adhesive	0.08	>16	- 5-100
6210		Acrylic pressure sensitive Adhesive	0.10	>18	- 5-100
JD015B		Acrylic pressure sensitive Adhesive	0.15	>18	- 5-100
6208B		Acrylic pressure sensitive Adhesive	0.08	>18	- 5-100
8208		Acrylic pressure sensitive Adhesive	0.08	Side A: 6-13 Side B: 15	- 5-100
6310K		Acrylic pressure sensitive Adhesive	0.10	Side A: 6-13 Side B: 22	- 5-100

* The above technical information and data are typical values only and should not be used for specification purposes.

Shelf Life

12 Months Storage at 23 °C and 65% Relative Humidity



Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.