

MEDIUM TEMPERATURE MASKING TAPE



Product Features

Semi-Bleached Crepe Paper Masking
Coated with Natural Rubber Adhesive

Application

Designed for transportation, marine and metal fabrication industries, as well as for wet sanding. It resists paint bleed-through, it can be used in temperatures up to 80°C and removes cleanly when the job is done

Colours



Light
Yellowish

Technical Data

Product	Max. Temp Resistance for 30min	Total Thickness	Initial Tack	Peel Adhesion	Tensile Strength	Elongation % at break
		(um)	(#)	(N/in)	(N/in)	
MTGP13-MT	80°C	130-140	8†	5†	50†	8%
MTGP15-MT	80°C	150-160	8†	6†	60†	8%

Product Characteristics

- Temperature-resistant up to 80°C
- Crepe paper backing provides easy tearing
- Excellent adhesion to metal, rubber, plastic and fiberglass
- Clean, flat edges for sharper paint lines
- Provides conformability on irregular surfaces and around corners
- Ideal for marking, temporary holding, wrapping and sealing
- Residue-free removal
- Solvent- and moisture-resistant

Product Sizes

Jumbo Roll Size :1250mm x 1500m

Paper Core Size :76mm

* Contact sales representative for available sizes

Shelf Life

12 Months Storage at 23°C and 65% Relative Humidity

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: www.gtgroup.com.my

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: info@gtgroup.com.my

