

# **Product Features**

Premium Grade PVC Film Coated with Solvent Rubber Adhesive

# Application

Ideal for corrosion protection and ground pipes such as air duct, water pipe and oil pipe line

### **Product Sizes**

Jumbo Roll Size :1250mm x 20m Paper Core Size :38/50/60/76mm

\* Contact sales representative for available sizes



#### Colours Yellow White Green Orange Red Blue A Black Matt Black Sky Blue Blue Yellow Black Yellow Red & Green & White Black & White

## **Technical Data**

White

Silver

Green Lines

Brown

Product	Total Thickness		Peel Adhesion	Tensile Strength	Elongation % at break	Unwinding strength
	(um)	(mil)	(N/in)	ASTM D-3759 (N/cm)	ASTM D-3759	(N/cm)
PWT13	130	5.1	3.75	20	130%	2-4
PWT15	150	5.9	3.75	22	140%	2-4
PWT18	180	7.1	3.75	25	150%	2-4

White Easy Tear

Brown Easy Tear

Yellow Easy Tear

### **Product Characteristics**

- Highly conformable, non-corrosive adhesive
- Easy unwinding
- Resistant to corrosive salt water, soil acids, alkalis and salts, common chemicals, chemical vapours
- Outdoor weathering and UV resistant
- Resistant to impact, abrasions, punctures, and tears
- Excellent insulating
- Conformable to awkward shapes

## **Shelf Life**

12 Months Storage at 23°C and 65% Relative Humidity

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.













