

# FILAMENT TAPE

## - SINGLE LINE



### Product Features

BOPP Film with Reinforced Glass Yarn  
Filament Coated with Synthetic  
Rubber Adhesive

### Application

Mainly used for heavy-duty bundling, packaging, palletizing and unitizing cartons. Ideally suited as a sealing and reinforcing material for long term transportation or shipping

### Product Sizes

Jumbo Roll Size :1060mm x 1000m  
Paper Core Size :76mm

\* Contact sales representative for available sizes



### Colours



White

### Technical Data

Product	Woven	Total Thickness		Initial Tack	Peel Adhesion		Tensile Strength		Elongation % at break
		(um)	(mil)	(#)	(N/in)	ASTM D-3330 (oz/in)	(N/in)	ASTM D-3759 (lb/in)	ASTM D-3759
FTSL12	Mono	120	4.7	5	8	29	450	100	12%
FTSL14	Mono	140	5.5	5	10	33	525	120	12%

### Product Characteristics

- High tensile strength ideal for strapping, bundling and reinforcing
- Moisture resistance, superior resistance against mildew and mold
- Provides excellent adhesion to corrugated cartons
- Excellent bonding performance due to well-known rubber adhesive of high flexibility
- High shear & excellent initial adhesion
- Hold instantly with minimum rubdown
- Nicks, abrasions and scuffing resistant
- Adhesive offers excellent balance of initial adhesion and long-term holding power
- Weather resistant
- Excellent performance in the roughest shipping and handling conditions

### Shelf Life

12 Months Storage at 23° C and 65% Relative Humidity

*Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.*



**GTG MANUFACTURING SDN. BHD. (968289-M)**

Website: [www.gtgroup.com.my](http://www.gtgroup.com.my)

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: [info@gtgroup.com.my](mailto:info@gtgroup.com.my)

