

# PET TAPE - SINGLE SIDED



## Product Features

PET tape is made of PET film as base material, coated with special semi-sensitive adhesive on one side

## Application

Can be used for mobile phone frame fixing, flat film switch bonding, automotive industry's ABS plastic parts fixing, rubber EPDM bonding, batteries in electronic equipment and lenses and windows' bonding, signage fixed, LCD reflective film splicing plastic film, low-energy plastic material bonding

## Product Sizes

\* Contact sales representative for available sizes



## Colours



White

## Technical Data

Product	Structure (from Top to Bottom)	Adhesive	Thickness	180° Peeling Force	Temperature resistance
			(mm)	(N/inch)	(°C)
G452	Transparent PET Acrylic pressure sensitive Adhesive PET Release film	Acrylic pressure sensitive Adhesive	0.065	>5	- 5~160
H448	Acrylic pressure sensitive Adhesive PET Release film	Acrylic pressure sensitive Adhesive	0.125	>22	- 5~160
L1237	Acrylic pressure sensitive Adhesive PET Release film	Acrylic pressure sensitive Adhesive	0.17	>15	- 5~160
6205	Acrylic pressure sensitive Adhesive Transparent PET/Black PET White Paper Release Paper	Acrylic pressure sensitive Adhesive	0.05	>10	- 5~100
6208	Acrylic pressure sensitive Adhesive Transparent PET/Black PET White Paper Release Paper	Acrylic pressure sensitive Adhesive	0.08	>16	- 5~100
6210	Acrylic pressure sensitive Adhesive Transparent PET/Black PET White Paper Release Paper	Acrylic pressure sensitive Adhesive	0.10	>18	- 5~100
JD015B	Acrylic pressure sensitive Adhesive Transparent PET/Black PET White Paper Release Paper	Acrylic pressure sensitive Adhesive	0.15	>18	- 5~100
6208B	Acrylic pressure sensitive Adhesive Transparent PET/Black PET White Paper Release Paper	Acrylic pressure sensitive Adhesive	0.08	>18	- 5~100
8208	Removable Adhesive Transparent PET Acrylic pressure sensitive Adhesive White Paper Release Paper	Acrylic pressure sensitive Adhesive	0.08	Side A: 6-13 Side B: 15	- 5~100
6310K	Removable Adhesive Transparent PET Acrylic pressure sensitive Adhesive White Paper Release Paper	Acrylic pressure sensitive Adhesive	0.10	Side A: 6-13 Side B: 22	- 5~100

\* The above technical information and data are typical values only and should not be used for specification purposes.

## Product Characteristics

- Scratch-proof, waterproof, easy to peel, no residue
- Reworkable, removable, good bonding strength for most materials, good initial viscosity

## Shelf Life

12 Months Storage at 23 °C and 65% Relative Humidity

*Disclaimer :* While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.



GTG MANUFACTURING SDN. BHD. (968289-M)

Website: [www.gtgroup.com.my](http://www.gtgroup.com.my)

Tel: +603-8725 9988 | Fax: +603-8725 9989 | Email: [info@gtgroup.com.my](mailto:info@gtgroup.com.my)

