



STICKY MAT

Product Features

Made of low density Polyethylene with water-based acrylic adhesive

Application

Sticky Mat normally used in clean rooms premises, museums, laboratory, premium showrooms, hospitals, world premiere, premium hotels and childcare centers.



Product Characteristics

- Provide a fast, convenient, reliable way to clean shoe soles or other items before entering a clean and sanitary area
- Significantly reduce traffic-borne contaminants
- Numbered corner tabs for easy tracking of remaining sheets
- Easy sheet -to-sheet removal
- Non-transferring adhesive
- Smooth, effective surface is not damaged by shoes, booties or cart wheels
- Glossy and no bubble surface, no wrinkles

Technical Data

Subject	Measured Value
Size	600*900mm ±3mm/customized
Thickness	0.025-0.05MM(2.5C-5C) ±0.004mm
Longitudinal Tensile Strength (MPa)	≥10
Transverse Tensile Strength (MPa)	≥8
Longitudinal split elongation rate (%)	≥250
Transverse split elongation rate (%)	≥750
180 degree peeling strength (g/25mm)	250±50g
Tackiness	Low/Middle/High
Layer	30 layers
Usage	Medical / Cleanroom and others



Product Sizes

Size : * Custom made size available

Disclaimer : While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose.